

Gigabit PoE Injector

SPECIFICATION

1. INPUT :

1.1 Input Voltage: 9Vdc to 36Vdc

1.2 Input Current: 1.85A at 12Vdc
0.90A at 24Vdc

2. OUTPUT :

2.1 Output Voltage & Current:

OUTPUT	+48V
Max. load	0.35A
Power	17W
Min. Load	0.01A
Load reg. %	5%
Line reg. %	1%
Ripple %	1%
Noise %	1%

TOTAL POWER :17W

Note 1: Noise bandwidth is from DC to 20Mhz. Ripple & Noise is measured by Paralleling a 0.1uF metalize capacitor on the test point.

3. EFFICIENCY : 75% min at Full Load , 12Vdc & 24Vdc Input Voltage

4. PROTECTION

4.1 Short Circuit Protection

Output Short GND Terminal will not damage the Power Supply and will Auto-Reset.

4.2 Input with Fuse Protection.

4.3 Safety Standard: meet UL1950, CSA 22.2 & TUV EN60950.

4.4 EMC : meet FCC Class B , EN55022 Class B, EN60945, EN50155

4.5 Over Current : 120% ~ 160% @12Vdc Input F.L

4.6 Dual Input Pin & Reverse Protection-----NO Work

5. GENERAL DESCRIPTION

5.1 Operation Temperature: - 25C - +75C


5.2 Storage Temperature: -40C - +85C


5.3 Operation Humidity: 5% - 90%

5.4 Cooling: Free air cooling

5.5 Dimensions: Plastic case 85*57*36 (L)*(W)*(H)

Metal case 82*56*35 (L)*(W)*(H)





6. Indicator :

6.1 Output Ready the LED will be “RED”

6.2 Output 802.3af OK the LED will be “GREEN”

7. RJ45 Connected and pin out: @1000MBASE

RJ-45 Input (Data Only)			RJ-45 Output (Data & Power)	
Pin	Symbol	Description	Symbol	Description
1	BI_DA+	Data Pair A+	BI_DA+	Data Pair A+
2	BI_DA-	Data Pair A-	BI_DA-	Data Pair A-
3	BI_DB+	Data Pair B+	BI_DB+	Data Pair B+
4	BI_DC+	Data Pair C+	+Vdc + BI_DC+	power(+)+Data Pair C+
5	BI_DC-	Data Pair C-	+Vdc + BI_DC-	power(+)+Data Pair C-
6	BI_DB-	Data Pair B-	BI_DB-	Data Pair B-
7	BI_DD+	Data Pair D+	-Vdc + BI_DD+	power(-)+Data Pair D+
8	BI_DD-	Data Pair D-	-Vdc + BI_DD-	power(-)+Data Pair D-

Note :

1. DC output gnd and Vin+/- should not be shorted to ground(FG).

