



KGS-124 Ver.C



24-Port 10/100/1000Base-T L2 Gigabit Ethernet Switch

Key Features:

- Provides 24 10/100/1000Mbps Gigabit Ethernet ports
- All ports support auto-negotiation and auto-MDI/MDI-X detection
- Supports full/half-duplex transfer mode for 10/100Mbps
- Supports full-duplex transfer mode for 1000Mbps
- Supports IEEE 802.3x flow control
- Provides full wire speed forwarding
- Store-and-Forward switching method
- MAC addresses table up to 8K entries
- Supports Jumbo frame up to 9K bytes
- Supports IEEE802.3az Energy Efficient Ethernet function

Specifications:

Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3x flow control, IEEE 802.3az EEE	
Number of Ports	24 x 10/100/1000Mbps auto-negotiation & auto-MDI/MDI-X ports	
Network Ports	10Base-T:	Cat.3, 4, 5 or higher (100 meters max.)
	100Base-TX:	Cat.5, 5e or higher (100 meters max.)
	1000Base-T:	Cat.5, 5e or higher (100 meters max.)
Network Data Transfer Rate	Ethernet:	10Mbps (Half-duplex) 20Mbps (Full-duplex)
	Fast Ethernet:	100Mbps (Half-duplex) 200Mbps (Full-duplex)
	Gigabit Ethernet:	2000Mbps (Full-duplex)
MAC Address Table	8K entries	
Jumbo Frame	9K bytes	
LEDs	Per Unit: Power Per Port: Speed/Link/ACT	
Environment	Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C Relative Humidity: 10% ~ 90% non-condensing	
Dimension	280 x 180 x 43.5 mm (WxDxH)	
Mounting Support	19" rack and wall mountable	
Power	100-240VAC, 50-60Hz	
Power Consumption	17.2W max.	
Approval	FCC Class A, CE mark Class A, LVD	



Katron Technologies Inc.
 15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
 Hsi-chih District, New Taipei City, Taiwan
 Tel: 886-2-2698-3878
 Fax: 886-2-2698-3873
 E-mail: kti@ktinet.com.tw
 URL: http://www.ktinet.com.tw

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
 This information is subject to change without prior notice.