



KS-219



9-Port 10/100 Switch with Gigabit Uplink

Key Features:

- Eight 10/100Mbps and one 1000Mbps auto-negotiation switched ports
- Full/half duplex transfer mode for each 10/100Mbps ports
- Full-duplex transfer mode for 1000Mbps Gigabit port
- Provides an additional 10/100 MDI-II jack for easy uplink via UTP cable
- Auto MDI-II/MDI-X for 1000Mbps Gigabit port
- Store-and-forward switching technology with full wire speed forwarding and filtering
- Supports broadcast storm control & broadcast storm filter
- IEEE 802.3x compliant flow control for full-duplex operation
- Back pressure control for half duplex operation
- Extensive diagnostic LED indicators, including HTTP, SMTP (E-mail) and ICQ activity status
- Desktop and 19" rack mountable

Specifications:

Standard	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T	
10/100/1000 ports	Shielded RJ-45	
Cable	10Base-T:	Cat. 3, 4, or 5 UTP cable (100m max.)
	100Base-TX:	Cat. 5 UTP cable (100m max.)
	1000Base-T:	Cat. 5 UTP cable (100m max.)
MAC Address	4K	
RAM Buffer	2Mbits	
LED Indicators	- Power, Alert - HTTP, SMTP (E-mail) and ICQ LED - 10/100 (Port 1-8), 10/100/1000 (Port 9) - Link/Activity, Full Duplex/Collision for each port	
Environment	Operating Temperature:	0° to 40° C
	Relative humidity:	10% to 90% non-condensing
Dimension	280 x 180 x 44.5mm (11.02 x 7.09 x 1.75inch)	
Power	100-240 VAC, 50/60 Hz	



KTI Networks Inc.

7400 Harwin Dr., Suite 120
 Houston, Texas 77036, U.S.A.
 Tel: 713-266-3891
 Fax: 713-266-3893
 E-mail: kti@ktinet.com
 URL: <http://www.ktinet.com>

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
 Hsi-chih, Taipei Hsien, Taiwan, R.O.C.
 Tel: 886-2-2698-3878
 Fax: 886-2-2698-3873
 E-mail: kti@ktinet.com.tw
 URL: <http://www.ktinet.com.tw>

Trademarks: All brand names are trademarks or registered trademarks of their respective holders. This information is subject to change without prior notice.