



# KGS-SOHO-8-B



## 8-Port 10/100/1000Base-T Gigabit Ethernet Switch

### Key Features:

- Provides 8 10/100/1000Mbps Gigabit Ethernet ports
- All 10/100/1000M ports support auto-negotiation and auto-MDI/MDI-X detection
- Supports full/half-duplex transfer mode for 10/100Mbps
- Supports full-duplex transfer mode for 1000Mbps
- Store-and-Forward switching method
- Wire-speed packet filtering and forwarding rate
- Supports IEEE 802.3x flow control
- Supports jumbo frame up to 9K bytes
- Supports IEEE 802.3az Energy Efficient Ethernet and Ethernet Green
- Supports 802.1p QoS classification

### Specifications:

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
Network Ports	8 10/100/1000Mbps Gigabit copper ports Shielded RJ-45, auto-negotiation, auto-MDI/MDI-X support
Network Cables	10Base-T: Cat.3, 4, 5 or higher ( 100 meters max. ) 100Base-TX: Cat.5, 5e or higher ( 100 meters max. ) 1000Base-T: Cat.5e or higher ( 100 meters max. )
Network Data Rate	Ethernet: 10Mbps (Half-duplex) 20Mbps (Full-duplex) Fast Ethernet: 100Mbps (Half-duplex) 200Mbps (Full-duplex) Gigabit Ethernet: 2000Mbps (Full-duplex)
MAC Address Table	4K entries
Buffer Memory	1.5M bits
LED Indication	Per unit: Power Per port: link/activity status
Environment	Operating Temperature: 0°C ~ 40°C Storage Temperature: -20°C ~ 70°C Relative Humidity: 10% ~ 90% non-condensing
Dimension	155 x 85 x 26 mm (WxDxH)
Power Input	+5V via external power adapter
Power Consumption	3.8W max. @+5V (DC IN)
Approval	FCC Class B, CE mark Class B



**Katron Technologies Inc.**  
15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,  
Hsi-chih District, New Taipei City, Taiwan  
Tel: 886-2-2698-3878  
Fax: 886-2-2698-3873  
E-mail: kti@ktinet.com.tw  
URL: <http://www.ktinet.com.tw>

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.  
This information is subject to change without prior notice.